



SAFETY DATA SHEET

425/G149 - CHLORINATED RUBBER BLUE, WHITE + PALE COLOURS also SWIMMING POOL PAINT

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name 425/G149 - CHLORINATED RUBBER BLUE, WHITE + PALE COLOURS also SWIMMING POOL PAINT
Product No. 425/G149/779, 1, +Pale Colours

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Paint.

1.3. Details of the supplier of the safety data sheet

Supplier TEAL & MACKRILL LIMITED
LOCKWOOD STREET
HULL
HU2 0HN
+44(0)1482 320194(T)
+44(0)1482 219266(F)
info@teamac.co.uk
Contact Person Technical Department - 08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri as above

1.4. Emergency telephone number

+44 (0) 1482 320194 (08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri)

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)
Physical and Chemical Hazards Flam. Liq. 3 - H226
Human health EUH066;STOT SE 3 - H335, H336
Environment Aquatic Chronic 2 - H411
Classification (1999/45/EEC) Xi;R37. N;R51/53. R10, R66, R67.

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

2.2. Label elements

Label In Accordance With (EC) No. 1272/2008



Signal Word Warning

Hazard Statements

H226 Flammable liquid and vapour.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

425/G149 - CHLORINATED RUBBER BLUE, WHITE + PALE COLOURS also SWIMMING POOL PAINT

Precautionary Statements

P102	Keep out of reach of children.
P101	If medical advice is needed, have product container or label at hand.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P501A	Dispose of contents/container to special waste collection point

Supplementary Precautionary Statements

P210	Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing vapour/spray.
P370+378	In case of fire: Use foam, carbon dioxide, dry powder or water fog for extinction.
P303+361+353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P391	Collect spillage.
P403+233	Store in a well-ventilated place. Keep container tightly closed.
P403+235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.

Supplemental label information

EUH066	Repeated exposure may cause skin dryness or cracking.
--------	---

2.3. Other hazards

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Hydrocarbons, C9, aromatics	30-60%
CAS-No.:	EC No.: 918-668-5 Registration Number: 01-2119455851-35-xxxx
Classification (EC 1272/2008) Flam. Liq. 3 - H226 EUH066 STOT SE 3 - H335, H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411	Classification (67/548/EEC) Xn;R65. Xi;R37. N;R51/53. R10,R66,R67.
Chlorinated polymer 20	10-30%
CAS-No.: 9006-03-5	EC No.:
Classification (EC 1272/2008) Not classified.	Classification (67/548/EEC) Not classified.

425/G149 - CHLORINATED RUBBER BLUE, WHITE + PALE COLOURS also SWIMMING POOL PAINT

Titanium Dioxide		10-30%
CAS-No.: 13463-67-7	EC No.: 236-675-5	Registration Number: 01-2119489379-17-xxxx
Classification (EC 1272/2008) Not classified.	Classification (67/548/EEC) Not classified.	
WHITE SPIRIT		1-5%
CAS-No.:	EC No.: 919-446-0	Registration Number: 01-2119458049-33-XXXX
Classification (EC 1272/2008) Flam. Liq. 3 - H226 EUH066 STOT SE 3 - H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411	Classification (67/548/EEC) Xn;R65. N;R51/53. R10,R66,R67.	
Low Aromatic White Spirit		1-5%
CAS-No.:	EC No.: 919-857-5	Registration Number: 01-2119463258-33-XXXX
Classification (EC 1272/2008) Flam. Liq. 3 - H226 EUH066 STOT SE 3 - H336 Asp. Tox. 1 - H304	Classification (67/548/EEC) Xn;R65. R10,R66,R67.	
C.I. Pigment Blue 15:3		<1%
CAS-No.: 147-14-8	EC No.: 205-685-1	
Classification (EC 1272/2008) Not classified.	Classification (67/548/EEC) Not classified.	
TOLUENE		<1%
CAS-No.: 108-88-3	EC No.: 203-625-9	Registration Number: 01-2119471310-51-0026
Classification (EC 1272/2008) Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 Repr. 2 - H361d STOT SE 3 - H336 STOT RE 2 - H373 Asp. Tox. 1 - H304	Classification (67/548/EEC) F;R11 Repr. Cat. 3;R63 Xn;R48/20,R65 Xi;R38 R67	
Yellow Iron Oxide		<1%
CAS-No.: 51274-00-1	EC No.:	Registration Number: 01-2119454754-33-xxxx
Classification (EC 1272/2008) Not classified.	Classification (67/548/EEC) Not classified.	

425/G149 - CHLORINATED RUBBER BLUE, WHITE + PALE COLOURS also SWIMMING POOL PAINT

ETHANOL		<0.1%
CAS-No.: 64-17-5	EC No.: 200-578-6	Registration Number: 01-2119457610-43-xxxx
Classification (EC 1272/2008) Flam. Liq. 2 - H225	Classification (67/548/EEC) F;R11	
METHANOL		<0.1%
CAS-No.: 67-56-1	EC No.: 200-659-6	
Classification (EC 1272/2008) Flam. Liq. 2 - H225 Acute Tox. 3 - H301 Acute Tox. 3 - H311 Acute Tox. 3 - H331 STOT SE 1 - H370	Classification (67/548/EEC) F;R11 T;R23/24/25,R39/23/24/25	
XYLENE, MIXED ISOMERS		<0.1%
CAS-No.: 1330-20-7	EC No.: 215-535-7	Registration Number: 01-2119488216-32-xxxx
Classification (EC 1272/2008) Flam. Liq. 3 - H226 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 STOT SE 3 - H335 STOT RE 2 - H373 Asp. Tox. 1 - H304	Classification (67/548/EEC) Xn;R20/21,R65. Xi;R36/37/38. R10.	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General information

Get medical attention if any discomfort continues.

Inhalation

Move into fresh air and keep at rest. Perform artificial respiration if breathing has stopped. Place unconscious person on the side in the recovery position and ensure breathing can take place.

Ingestion

Get medical attention immediately! DO NOT INDUCE VOMITING!

Skin contact

Remove contaminated clothing immediately and wash skin with soap and water. DO NOT use solvents or thinners

Eye contact

Make sure to remove any contact lenses from the eyes before rinsing. Immediately flush with plenty of water or eyewash solution for up to 10 minutes. Consult a physician for specific advice.

4.2. Most important symptoms and effects, both acute and delayed

General information

If adverse symptoms develop as described the casualty should be transferred to hospital as soon as possible.

4.3. Indication of any immediate medical attention and special treatment needed

No specific first aid measures noted.

425/G149 - CHLORINATED RUBBER BLUE, WHITE + PALE COLOURS also SWIMMING POOL PAINT**SECTION 5: FIREFIGHTING MEASURES****5.1. Extinguishing media**

Extinguishing media

Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards

In case of fire, toxic gases may be formed (COx, NOx). Fire creates: Acrid smoke/fumes of: Carbon monoxide (CO). Carbon dioxide (CO2). Nitrous gases (NOx).

5.3. Advice for firefighters

Protective equipment for fire-fighters

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

SECTION 6: ACCIDENTAL RELEASE MEASURES**6.1. Personal precautions, protective equipment and emergency procedures**

Avoid inhalation of vapours and contact with skin and eyes. Ensure suitable personal protection (including respiratory protection) during removal of spillages in a confined area.

6.2. Environmental precautions

Do not allow to enter drains, sewers or watercourses. Contain spillages with sand, earth or any suitable adsorbent material. Spillages or uncontrolled discharges into watercourses must be IMMEDIATELY alerted to the Environmental Agency or other appropriate regulatory body.

6.3. Methods and material for containment and cleaning up

Collect with absorbent, non-combustible material into suitable containers. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

6.4. Reference to other sections

For personal protection, see section 8.

SECTION 7: HANDLING AND STORAGE**7.1. Precautions for safe handling**

Read and follow manufacturer's recommendations. Eliminate all sources of ignition. Risk of vapour concentration on the floor and in low-lying areas. Use explosion proof electric equipment. Do not eat, drink or smoke when using the product. Avoid inhalation of vapours/spray and contact with skin and eyes. The Manual Handling Operations Regulations may apply to the handling of containers of this product. To assist employers, the following method of calculating the weight for any pack size is given. Take the pack size volume in litres and multiply this figure by the specific gravity value given in section 9. This will give the net weight of the coating in kilograms. Allowance will then have to be made for the immediate packaging to give an approximate gross weight.

7.2. Conditions for safe storage, including any incompatibilities

Keep containers tightly closed. Keep upright. Protect from light, including direct sunrays. Store in closed original container at temperatures between 5°C and 25°C. Store separated from: Oxidising material. Acids. Alkalis.

Storage Class

Flammable liquid storage. The storage and use of this product is subject to the Dangerous Substances and Explosive Atmospheres Regulations (DSEAR). The requirements are given in the HSE Approved Code of Practice and Guidance, Storage of Dangerous Substances: DSEAR. Up to 250 litres of liquids with a flashpoint above 32C but below 55C may be kept in a workroom provided they are kept in closed containers in a marked, fire-resisting cupboard or bin. Larger quantities must be kept in a separate, marked storeroom conforming to the structural requirements contained in the HSE guidance note Storage of Flammable Liquids in Containers.

7.3. Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

425/G149 - CHLORINATED RUBBER BLUE, WHITE + PALE COLOURS also SWIMMING POOL PAINT**8.1. Control parameters**

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
C.I. Pigment Blue 15:3	MEL		1.5 mg/m3 resp.dust			
Chlorinated polymer 20	WEL		10 mg/m3 total dust			
ETHANOL	WEL	1000 ppm	1920 mg/m3			
Hydrocarbons, C9, aromatics	WEL	19 ppm	100 mg/m3			
Low Aromatic White Spirit	WEL		1000 mg/m3			
METHANOL	WEL	200 ppm(Sk)	266 mg/m3(Sk)	250 ppm(Sk)	333 mg/m3(Sk)	
Titanium Dioxide	WEL		10 mg/m3			
TOLUENE	WEL	50 ppm	191 mg/m3	100 ppm	384 mg/m3	Sk
WHITE SPIRIT	WEL		350 mg/m3			
XYLENE, MIXED ISOMERS	WEL	50 ppm	220 mg/m3	100 ppm	441 mg/m3	Sk
Yellow Iron Oxide	WEL		10 mg/m3 total dust			

WEL = Workplace Exposure Limit.

Sk = Can be absorbed through skin.

425/G149 - CHLORINATED RUBBER BLUE, WHITE + PALE COLOURS also SWIMMING POOL PAINT**Yellow Iron Oxide (CAS: 51274-00-1)**

DNEL				
Industry	Inhalation.	Long Term	Systemic Effects	10 (inhalable) mg/m3
Industry	Inhalation.	Long Term	Local Effects	10 mg/m3

Titanium Dioxide (CAS: 13463-67-7)

DNEL				
Industry	Inhalation.	Long Term	Local Effects	10 mg/m3
Consumer	Oral	Long Term	Systemic Effects	700 mg/kg/day
PNEC				
Freshwater	>1	mg/l		
Sediment (Freshwater)	>=1000	mg/kg		
Marinewater	0.127	mg/l		
Sediment (Marinewater)	>=100	mg/kg		
Soil	100	mg/kg		
STP	100	mg/kg		

Low Aromatic White Spirit

DNEL				
Consumer	Oral	Long Term	Systemic Effects	300 mg/kg/day
Consumer	Dermal	Long Term	Systemic Effects	300 mg/kg/day
Industry	Dermal	Long Term	Systemic Effects	300 mg/kg/day
Industry	Inhalation.	Long Term	Systemic Effects	1500 mg/m3
Consumer	Inhalation.	Long Term	Systemic Effects	900 mg/m3

No PNEC available. Substance is a hydrocarbon UVCB. Standard tests for this endpoint are intended for single substances and are not appropriate for the risk assessment of this complex substance.

WHITE SPIRIT

DNEL				
Consumer	Oral	Long Term	Systemic Effects	1040 mg/kg/day
Consumer	Dermal	Long Term	Systemic Effects	1040 mg/kg/day
Consumer	Inhalation.	Long Term	Systemic Effects	710 mg/m3
Consumer	Inhalation.	Short Term	Systemic Effects	570 mg/m3
Industry	Inhalation.	Short Term	Systemic Effects	570 mg/m3
Industry	Inhalation.	Long Term	Systemic Effects	1980 mg/m3
Industry	Dermal	Long Term	Systemic Effects	1056 mg/kg/day

Hydrocarbons, C9, aromatics

DNEL				
Consumer	Oral	Long Term	Systemic Effects	11 mg/kg/day
Consumer	Dermal	Long Term	Systemic Effects	11 mg/kg/day
Consumer	Inhalation.	Long Term	Systemic Effects	32 mg/m3
Industry	Dermal	Long Term	Systemic Effects	25 mg/kg/day
Industry	Inhalation.	Long Term	Systemic Effects	100 mg/m3

XYLENE, MIXED ISOMERS (CAS: 1330-20-7)

DNEL				
Consumer	Oral	Long Term	Systemic Effects	12.5 mg/kg/day
Consumer	Dermal	Long Term	Systemic Effects	1872 mg/kg/day
Consumer	Inhalation.	Long Term	Systemic Effects	65.3 mg/m3
Consumer	Inhalation.	Short Term	260	mg/m3
Industry	Dermal	Long Term	Systemic Effects	3182 mg/kg/day
Industry	Inhalation.	Long Term	Systemic Effects	221 mg/m3
Industry	Inhalation.	Short Term	442	mg/m3

No PNEC available. Substance is a hydrocarbon UVCB. Standard tests for this endpoint are intended for single substances and are not appropriate for the risk assessment of this complex substance.

8.2. Exposure controls

Protective equipment



Process conditions

Use engineering controls to reduce air contamination to permissible exposure level.

Engineering measures

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.

Respiratory equipment

No specific recommendation made, but respiratory protection must be used if the general level exceeds the recommended occupational exposure limit. In case of inadequate ventilation, use air-supplied full-mask.

425/G149 - CHLORINATED RUBBER BLUE, WHITE + PALE COLOURS also SWIMMING POOL PAINT**Hand protection**

Wear protective gloves. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material. Barrier cream applied before work may make it easier to clean the skin after exposure, but does not prevent absorption through the skin.

Eye protection

Wear splash-proof eye goggles to prevent any possibility of eye contact.

Hygiene measures

Wash promptly with soap & water if skin becomes contaminated. Remove contaminated clothing and wash the skin thoroughly with soap and water after work.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**9.1. Information on basic physical and chemical properties**

Appearance	Viscous Coloured liquid.
Colour	Blue. White. Light (or pale). Various colours
Odour	of solvents
Solubility	Insoluble in water
Relative density	1.08 - 1.25 @ 20 C
Vapour density (air=1)	heavier than air
Viscosity	3.0 (ICI Rotothinner) Ps @ 25 C
Flash point (°C)	40 approx. CC (Closed cup).
Flammability Limit - Upper(%)	0.8

9.2. Other information

Volatility Description	Volatile
Volatile Organic Compound (VOC)	560 - 620 depending on colour g/litre

SECTION 10: STABILITY AND REACTIVITY**10.1. Reactivity**

No specific reactivity hazards associated with this product.

10.2. Chemical stability

Stable under normal temperature conditions and recommended use.

10.3. Possibility of hazardous reactions

Not determined.

10.4. Conditions to avoid

Avoid heat, flames and other sources of ignition. Avoid contact with acids and oxidising substances.

10.5. Incompatible materials

Materials To Avoid

Strong alkalis. Strong acids. Strong oxidising substances.

10.6. Hazardous decomposition products

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

SECTION 11: TOXICOLOGICAL INFORMATION**11.1. Information on toxicological effects**

Toxicological information

No data recorded.

425/G149 - CHLORINATED RUBBER BLUE, WHITE + PALE COLOURS also SWIMMING POOL PAINT

General information

Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

Inhalation

May cause irritation to the respiratory system. In high concentrations, vapours are narcotic and may cause headache, fatigue, dizziness and nausea. Contains organic solvents which in case of overexposure may depress the central nervous system causing dizziness and intoxication.

Ingestion

Liquid irritates mucous membranes and may cause abdominal pain if swallowed. May irritate and cause stomach pain, vomiting and diarrhoea. May cause nausea, headache, dizziness and intoxication.

Skin contact

May be absorbed through the skin. Acts as a defatting agent on skin. May cause cracking of skin, and eczema.

Eye contact

Irritation of eyes and mucous membranes.

Route of entry

Inhalation. Skin absorption. Ingestion. Skin and/or eye contact.

Toxicological information on ingredients.

425/G149 - CHLORINATED RUBBER BLUE, WHITE + PALE COLOURS also SWIMMING POOL PAINT
Low Aromatic White SpiritAcute toxicity:

Acute Toxicity (Oral LD50)

> 5000 mg/kg Rat

Acute Toxicity (Dermal LD50)

> 5000 mg/kg Rabbit

Acute Toxicity (Inhalation LC50)

> 5 mg/l (vapours) Rat 4 hours

Skin Corrosion/Irritation:

Erythema/scar score

Very slight erythema -barely perceptible (1). Well defined erythema (2).

Oedema score

No oedema (0).

Slightly irritating.

Serious eye damage/irritation:

Not Irritating.

Respiratory or skin sensitisation:

Not sensitising.

Skin sensitisation

Guinea pig maximization test (GPMT): Guinea Pig

Not Sensitising.

Germ cell mutagenicity:

Genotoxicity - In Vitro

Chromosome aberration:

Negative.

This substance has no evidence of mutagenic properties.

Carcinogenicity:

Inhalation. Rat

This substance has no evidence of carcinogenic properties. Does not contain any substances known to be carcinogenic.

Reproductive Toxicity:

Reproductive Toxicity - Fertility

Fertility: Inhalation. Rat

This substance has no evidence of toxicity to reproduction.

Reproductive Toxicity - Development

Developmental toxicity: Inhalation. Rat

This substance has no evidence of toxicity to reproduction.

Specific target organ toxicity - repeated exposure:

STOT - Repeated exposure

Not available.

Aspiration hazard:

Viscosity

Kinematic viscosity <= 20.5 mm²/s.

Inhalation

Vapours may cause drowsiness and dizziness. Central nervous system depression.

Ingestion

Harmful: danger of serious damage to health by prolonged exposure if swallowed.

Skin contact

Acts as a defatting agent on skin. May cause cracking of skin, and eczema.

425/G149 - CHLORINATED RUBBER BLUE, WHITE + PALE COLOURS also SWIMMING POOL PAINT

Eye contact

No specific health warnings noted.

Route of entry

Inhalation. Ingestion.

425/G149 - CHLORINATED RUBBER BLUE, WHITE + PALE COLOURS also SWIMMING POOL PAINT
WHITE SPIRIT**Other Health Effects**

This substance has no evidence of carcinogenic properties.

Acute toxicity:

Acute Toxicity (Oral LD50)

> 15000 mg/kg Rat

Minimally toxic via ingestion

Acute Toxicity (Dermal LD50)

~ 3400 mg/kg Rabbit

Not corrosive to skin Not irritating

Acute Toxicity (Inhalation LC50)

> 13.1 mg/l (vapours) Rat 4 hours

Serious eye damage/irritation:

Not Irritating.

Respiratory or skin sensitisation:

Respiratory sensitisation

Not determined.

There is evidence that the material can lead to respiratory hypersensitivity.

Not Sensitising.

Carcinogenicity:

Carcinogenicity

NOAEL 300 mg/kg Oral Rat

Reproductive Toxicity:

Reproductive Toxicity - Fertility

One-generation study: NOAEL >3000 mg/kg/day Oral Rat P

Reproductive Toxicity - Development

Developmental toxicity: NOAEC >300 ppm Inhalation. Rat

Specific target organ toxicity - single exposure:

Target Organs

Central nervous system

Specific target organ toxicity - repeated exposure:

STOT - Repeated exposure

NOAEL 1056 mg/kg Oral Rat

Aspiration hazard:

Viscosity

Kinematic viscosity <= 20.5 mm²/s.

Inhalation

No specific health warnings noted.

Ingestion

Harmful: may cause lung damage if swallowed. May cause stomach pain or vomiting.

Skin contact

May cause defatting of the skin, but is not an irritant. Not a skin sensitiser.

Eye contact

No specific health warnings noted.

Route of entry

Skin and/or eye contact. Inhalation.

Target Organs

Central nervous system

425/G149 - CHLORINATED RUBBER BLUE, WHITE + PALE COLOURS also SWIMMING POOL PAINT

Hydrocarbons, C9, aromatics

Acute toxicity:

Acute Toxicity (Oral LD50)

~ 3592 mg/kg Rat

Acute Toxicity (Dermal LD50)

> 3160 mg/kg Rabbit

Acute Toxicity (Inhalation LC50)

> 6193 mg/l (vapours) Rat 4 hours

Serious eye damage/irritation:

Slightly Irritating.

Respiratory or skin sensitisation:

Not sensitising.

Not Sensitising.

Carcinogenicity:

This substance has no evidence of carcinogenic properties.

Specific target organ toxicity - single exposure:

Target Organs

Central nervous system Respiratory system, lungs

Aspiration hazard:

Kinematic viscosity <= 20.5 mm²/s.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity

There are no data on the ecotoxicity of this product. The product contains substances which are toxic to aquatic organisms and which may cause long term adverse effects in the aquatic environment.

12.1. Toxicity

425/G149 - CHLORINATED RUBBER BLUE, WHITE + PALE COLOURS also SWIMMING POOL PAINTEcological information on ingredients.**Low Aromatic White Spirit**

Acute Toxicity - Fish

LC50 96 hours > 1000 mg/l Onchorhynchus mykiss (Rainbow trout)

Substance did not cause acute toxicity to fish

EC 50, 48 Hrs, Daphnia, mg/l

>1000

Substance did not cause acute toxicity to the freshwater invertebrates

Acute Toxicity - Aquatic Plants

EC50 72 hours > 1000 mg/l Freshwater algae

Substance did not cause acute toxicity to the freshwater green algae

EC50 > 100 mg/l Activated sludge

Chronic Toxicity - Fish Early life Stage

NOEC 28 days 0.131 mg/l Onchorhynchus mykiss (Rainbow trout)

Chronic Toxicity - Aquatic Invertebrates

NOEC 28 days 0.23 mg/l Daphnia magna

WHITE SPIRIT

Dangerous for the environment if discharged into watercourses Toxic to aquatic organisms

LC 50, 96 Hrs, Fish mg/l

10 - 30

EC 50, 48 Hrs, Daphnia, mg/l

10 - 22

IC 50, 72 Hrs, Algae, mg/l

4.6 - 10

Chronic Toxicity - Aquatic Invertebrates

NOEC 21 days < 0.28 mg/l Daphnia magna

Hydrocarbons, C9, aromatics

Toxic to aquatic organisms

LC 50, 96 Hrs, Fish mg/l

9.2

EC 50, 48 Hrs, Daphnia, mg/l

3.2

12.2. Persistence and degradability

Degradability

No data available.

Ecological information on ingredients.**Low Aromatic White Spirit**

Degradability

The product is easily biodegradable.

Oxidises rapidly by photo-chemical reactions in air

Biodegradation

Degradation (80%) 28 days

Test - 301F Ready Biodegradability - Manometric Respiratory Test

WHITE SPIRIT

Degradability

The product is easily biodegradable.

Biodegradation

Degradation (75%) 28 days

Hydrocarbons, C9, aromatics

Degradability

The product is easily biodegradable.

Biodegradation

Degradation (78%) 28 days

12.3. Bioaccumulative potential

Bioaccumulative potential

No data available on bioaccumulation.

425/G149 - CHLORINATED RUBBER BLUE, WHITE + PALE COLOURS also SWIMMING POOL PAINTEcological information on ingredients.**Low Aromatic White Spirit**

Bioaccumulative potential

The product contains potentially bioaccumulating substances.

Partition coefficient

5 - 6.7

WHITE SPIRIT

Bioaccumulation factor

Scientifically unjustified.

Substance is a hydrocarbon UVCB. Standard tests for this endpoint are intended for single substances and are not appropriate for this complex substance.

Hydrocarbons, C9, aromatics

Bioaccumulative potential

No data available on bioaccumulation.

12.4. Mobility in soil

Mobility:

The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces.

Ecological information on ingredients.**Low Aromatic White Spirit**

Mobility:

The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces. Readily absorbed into soil.

Adsorption/Desorption Coefficient

Not available.

Surface tension

24.5 mN/m 20 °C

WHITE SPIRIT

Adsorption/Desorption Coefficient

Scientifically unjustified.

Volatilisation is dependent on Henry's Law constant (HLC) which is not applicable to complex substances.

Hydrocarbons, C9, aromatics

Mobility:

The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces.

12.5. Results of PBT and vPvB assessmentEcological information on ingredients.**Low Aromatic White Spirit**

Not Classified as PBT/vPvB by current EU criteria.

WHITE SPIRIT

Not Classified as PBT/vPvB by current EU criteria.

Hydrocarbons, C9, aromatics

Not Classified as PBT/vPvB by current EU criteria.

12.6. Other adverse effects

The product contains volatile, organic compounds which have a photochemical ozone creation potential.

Ecological information on ingredients.**Low Aromatic White Spirit**

Not known.

WHITE SPIRIT

This substance may contribute to ozone formation in the near surface atmosphere. However, the photochemical formation of ozone depends on a complex interaction of other atmospheric pollutant sources and environmental conditions. Therefore, the contribution of this substance to ozone formation is outside the scope of this substance assessment and is more appropriately addressed via EU air quality directives.

Hydrocarbons, C9, aromatics

Not determined.

425/G149 - CHLORINATED RUBBER BLUE, WHITE + PALE COLOURS also SWIMMING POOL PAINT**SECTION 13: DISPOSAL CONSIDERATIONS**

General information

Waste to be treated as controlled waste. Disposal to licensed waste disposal site in accordance with local Waste Disposal Authority.

13.1. Waste treatment methods

Do not allow runoff to sewer, waterway or ground.

Waste Class

When this coating, in its liquid state, as supplied, becomes a waste, it is categorised as hazardous waste, with code 08 01 11* (SOLVENT BASED LIQUID WASTE). Part-used containers, not drained and/or rigorously scraped out and containing dried residues of the supplied coating, are categorised as hazardous waste, with code 08 01 11* (SOLVENT BASED LIQUID WASTE). If mixed with other wastes, the above waste code may not be applicable. Used containers, drained and/or rigorously scraped out and containing dry residues of the supplied coating, are categorised as non-hazardous waste, with code 15 01 02 (plastic packaging) or 15 01 04 (metal packaging).

SECTION 14: TRANSPORT INFORMATION

General This product is packed in accordance with the Limited Quantity Provisions of CDGCPL2, ADR and IMDG.

14.1. UN number

UN No. (ADR/RID/ADN)	1263
UN No. (IMDG)	1263
UN No. (ICAO)	1263

14.2. UN proper shipping name

Proper Shipping Name	Contains 1, 2, 4-Trimethylbenzene, Class 3, PG III, (41 °C c.c.) MARINE POLLUTANT
Proper Shipping Name	PAINT

14.3. Transport hazard class(es)

ADR/RID/ADN Class	1263
ADR/RID/ADN Class	Class 3: Flammable liquids.
IMDG Class	3
ICAO Class/Division	3
Transport Labels	

**14.4. Packing group**

ADR/RID/ADN Packing group	III
IMDG Packing group	III
ICAO Packing group	III

14.5. Environmental hazards

Environmentally Hazardous Substance/Marine Pollutant

425/G149 - CHLORINATED RUBBER BLUE, WHITE + PALE COLOURS also SWIMMING POOL PAINT**14.6. Special precautions for user**

EMS F-E, S-E

Tunnel Restriction Code (D/E)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable.

SECTION 15: REGULATORY INFORMATION**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Uk Regulatory References

The Control of Substances Hazardous to Health Regulations 2002 (S.I 2002 No. 2677) with amendments.

Statutory Instruments

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (S.I 2009 No. 716). Control of Substances Hazardous to Health.

Approved Code Of Practice

Safety Data Sheets for Substances and Preparations. Classification and Labelling of Substances and Preparations Dangerous for Supply. Dangerous Substances and Explosive Atmospheres Regulations 2002 [L138]

Guidance Notes

Workplace Exposure Limits EH40. CHIP for everyone HSG(108).

EU Legislation

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments.

National Regulations

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002. No. 1689.

15.2. Chemical Safety Assessment

No chemical safety assessment has been carried out.

SECTION 16: OTHER INFORMATION

Revision Comments

Issued in new format for Reach compliance in accordance with EC 1272/2008 Issued in accordance with Annex II to REACH, as amended by Commission Regulation (EU) No. 453/2010 Update for CLP labelling.

Issued By Technical Dept. (P.E.)

Revision Date 11/05/2015

Revision 8

Supersedes date 29/11/2012

SDS No. 10731

Safety Data Sheet Status Approved.

Date Date Printed

Signature Initials

425/G149 - CHLORINATED RUBBER BLUE, WHITE + PALE COLOURS also SWIMMING POOL PAINT

Risk Phrases In Full

R10	Flammable.
R20/21	Harmful by inhalation and in contact with skin.
R48/20	Harmful: danger of serious damage to health by prolonged exposure through inhalation.
R65	Harmful: may cause lung damage if swallowed.
R11	Highly flammable
R36/37/38	Irritating to eyes, respiratory system and skin.
R37	Irritating to respiratory system.
R38	Irritating to skin.
NC	Not classified.
R63	Possible risk of harm to the unborn child.
R66	Repeated exposure may cause skin dryness or cracking.
R23/24/25	Toxic by inhalation, in contact with skin and if swallowed.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R39/23/24/25	Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed.
R67	Vapours may cause drowsiness and dizziness.

Hazard Statements In Full

H370	Causes damage to organs <<Organs>>.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H226	Flammable liquid and vapour.
H332	Harmful if inhaled.
H312	Harmful in contact with skin.
H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H373	May cause damage to organs <<Organs>> through prolonged or repeated exposure if inhaled.
H373	May cause damage to organs <<Organs>> through prolonged or repeated exposure.
H336	May cause drowsiness or dizziness.
H335	May cause respiratory irritation.
EUH066	Repeated exposure may cause skin dryness or cracking.
H361d	Suspected of damaging the unborn child.
H331	Toxic if inhaled.
H301	Toxic if swallowed.
H311	Toxic in contact with skin.
H411	Toxic to aquatic life with long lasting effects.

Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.